


## Allgemeine Information

## Aussen - Stehleuchten



|               |                             |
|---------------|-----------------------------|
| Ean           | 8021696254388               |
| Artikel       | AGOS PT H60 ANTRACITE 3000K |
| Installation  | Stehleuchten                |
| Garantie      | 5 years                     |
| Bruttogewicht | 1.41 kg                     |
| Volumen       | 0.012719 m³                 |

## Technische Information

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Nettogewicht       | 0.95 kg                                                                        |
| Isolationsklasse   | I                                                                              |
| Schutzindex        | IP54                                                                           |
| Einhaltung         | CE                                                                             |
| Betriebstemperatur | -15° ~ +45 °C                                                                  |
| Dimmer             | Non-dimmable, On-Off                                                           |
| Leistung           | 220-240 V AC 50 Hz                                                             |
| Energieversorgung  | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Quellinfo

|                          |                       |
|--------------------------|-----------------------|
| Integrierte Quelle       | Integrated LED module |
| Austauschbare Quelle     | No                    |
| Leistung                 | 6,5 W                 |
| Emissionen               | Direct                |
| Maximaler Verbrauch      | max 6,5 W             |
| Merkmale LED             | LED SMD               |
| CCT LED                  | 3000 K                |
| Dauer LED (t. 25°C)      | 25000 h               |
| CRI                      | > 90                  |
| SDCM                     | 3                     |
| Lichtstrahlwinkel        | 120*70°               |
| Lichtstrahlfluss         | 670 lm                |
| Nützlicher Lichtstrom    | 560 lm                |
| Photobiologisches Risiko | 1                     |