

## Allgemeine Information


## Aussen - Wandleuchten



|               |                          |
|---------------|--------------------------|
| Ean           | 8021696250946            |
| Artikel       | ARGO AP2 ANTRACITE 3000K |
| Installation  | Wandleuchten             |
| Garantie      | 5 years                  |
| Bruttogewicht | 0.64 kg                  |
| Volumen       | 0.00105 m³               |

## Technische Information

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Nettogewicht       | 0.6 kg                                                                         |
| Isolationsklasse   | I                                                                              |
| Schutzindex        | IP65                                                                           |
| Einhaltung         | CE                                                                             |
| Betriebstemperatur | -15° ~ +45 °C                                                                  |
| Dimmer             | Non-dimmable, On-Off                                                           |
| Leistung           | 220-240 V AC 50/60 Hz                                                          |
| Energieversorgung  | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |
| Lastwiderstand     | IK06                                                                           |



## Quellinfo

|                          |                       |
|--------------------------|-----------------------|
| Integrierte Quelle       | Integrated LED module |
| Austauschbare Quelle     | No                    |
| Leistung                 | 11 W                  |
| Emissionen               | Direct + Indirect     |
| Maximaler Verbrauch      | max 11 W              |
| Merkmale LED             | LED COB CREE          |
| CCT LED                  | 3000 K                |
| Dauer LED (t. 25°C)      | 30000 h               |
| CRI                      | > 90                  |
| SDCM                     | 3                     |
| Lichtstrahlwinkel        | 85+85°                |
| Lichtstrahlfluss         | 1000 lm               |
| Nützlicher Lichtstrom    | 780 lm                |
| Photobiologisches Risiko | 1                     |