

## Allgemeine Information

## Innen - Wandleuchten



|               |                       |
|---------------|-----------------------|
| Ean           | 8021696260662         |
| Artikel       | BEAN AP SQUARE OTTONE |
| Installation  | Wandleuchten          |
| Garantie      | 5 years               |
| Bruttogewicht | 0.22 kg               |
| Volumen       | 0.000704 m³           |

## Technische Information



|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Nettogewicht       | 0.18 kg                                                                        |
| Isolationsklasse   | I                                                                              |
| Schutzindex        | IP20                                                                           |
| Einhaltung         | CE                                                                             |
| Betriebstemperatur | 0° ~ +40 °C                                                                    |
| Dimmer             | Non-dimmable, On-Off                                                           |
| Leistung           | 100-240 V AC 50/60 Hz                                                          |
| Energieversorgung  | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Quellinfo

|                          |                                           |
|--------------------------|-------------------------------------------|
| Integrierte Quelle       | Integrated LED module                     |
| Austauschbare Quelle     | Replaceable (by qualified operators only) |
| Leistung                 | LED 3 W                                   |
| Emissionen               | Direct                                    |
| Maximaler Verbrauch      | max 3 W                                   |
| Merkmale LED             | LED SMD CREE                              |
| CCT LED                  | 3000 K                                    |
| Dauer LED (t. 25°C)      | 30000 h                                   |
| CRI                      | > 90                                      |
| SDCM                     | 3                                         |
| Lichtstrahlwinkel        | 25°                                       |
| Lichtstrahlfluss         | 200 lm                                    |
| Nützlicher Lichtstrom    | 180 lm                                    |
| Photobiologisches Risiko | 2                                         |