


## Allgemeine Information

## Technisch - Systeme



|               |                                            |
|---------------|--------------------------------------------|
| Ean           | 8021696330730                              |
| Artikel       | EGO TRACK 10W 20°-40° ZOOM 3000K ON-OFF BK |
| Installation  | Systeme                                    |
| Garantie      | 5 years                                    |
| Bruttogewicht | 0.61 kg                                    |
| Volumen       | 0.003744 m³                                |

## Technische Information

|                    |                                       |
|--------------------|---------------------------------------|
| Nettogewicht       | 0.46 kg                               |
| Isolationsklasse   | III                                   |
| Schutzindex        | IP20                                  |
| Einhaltung         | CE                                    |
| Betriebstemperatur | 0° ~ +40 °C                           |
| Dimmer             | Non-dimmable, On-Off                  |
| Leistung           | 48 V DC                               |
| Energieversorgung  | Required, remoted, not included<br>NO |

## Quellinfo

|                          |                                           |
|--------------------------|-------------------------------------------|
| Integrierte Quelle       | Integrated LED module                     |
| Austauschbare Quelle     | Replaceable (by qualified operators only) |
| Leistung                 | 10 W                                      |
| Emissionen               | Direct                                    |
| Maximaler Verbrauch      | max 10 W                                  |
| Merkmale LED             | LED COB CITIZEN                           |
| CCT LED                  | 3000 K                                    |
| Dauer LED (t. 25°C)      | 50000 h                                   |
| CRI                      | > 90                                      |
| SDCM                     | 3                                         |
| Lichtstrahlwinkel        | 20-40°                                    |
| Lichtstrahlfluss         | 900 lm                                    |
| Nützlicher Lichtstrom    | 750 lm                                    |
| Photobiologisches Risiko | 1                                         |