



## Allgemeine Information

### Technisch - Systeme

|               |                                |
|---------------|--------------------------------|
| Ean           | 8021696192666                  |
| Artikel       | FLUO BI-EMISSION 1200 3000K WH |
| Installation  | Systeme                        |
| Garantie      | 5 years                        |
| Bruttogewicht | 4.89 kg                        |
| Volumen       | 0.018383 m³                    |

## Technische Information

|                         |                                                                                          |
|-------------------------|------------------------------------------------------------------------------------------|
| Nettogewicht            | 2.89 kg                                                                                  |
| Isolationsklasse        | I                                                                                        |
| Schutzindex             | IP20                                                                                     |
| Einhaltung              | CE                                                                                       |
| Betriebstemperatur      | 0° ~ +40 °C                                                                              |
| Dimmer                  | Non-dimmable, On-Off                                                                     |
| Leistung                | 220-240 V AC 50/60 Hz                                                                    |
| Energieversorgung       | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic |
| Zubehör nicht inklusive | Mounting kit (suspension), Dimmable drivers kit,<br>Structure connector                  |



## Quellinfo

|                          |                       |
|--------------------------|-----------------------|
| Integrierte Quelle       | Integrated LED module |
| Austauschbare Quelle     | No                    |
| Leistung                 | 40 W                  |
| Emissionen               | Direct + Indirect     |
| Maximaler Verbrauch      | max 40 W              |
| Merkmale LED             | LED SMD SAMSUNG       |
| CCT LED                  | 3000 K                |
| Dauer LED (t. 25°C)      | 50000 h               |
| CRI                      | > 90                  |
| SDCM                     | 3                     |
| Lichtstrahlwinkel        | 105+105°              |
| Lichtstrahlfluss         | 5500 lm               |
| Nützlicher Lichtstrom    | 3820 lm               |
| Photobiologisches Risiko | 1                     |