



Allgemeine Information

Technisch - Systeme

Ean	8021696192604
Artikel	FLUO WIDE 1800 4000K WH
Installation	Systeme
Garantie	5 years
Bruttogewicht	6.64 kg
Volumen	0.0403 m ³

Technische Information

Nettogewicht	4.42 kg
Isolationsklasse	I
Schutzindex	IP20
Einhaltung	CE
Betriebstemperatur	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Leistung	220-240 V AC 50/60 Hz
Energieversorgung	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Zubehör nicht inklusive	Mounting kit (suspension, recessed, surface), Dimmable driver, Luminous corner, Structure connector



Quellinfo

Integrierte Quelle	Integrated LED module
Austauschbare Quelle	Replaceable (by qualified operators only)
Leistung	36 W
Emissionen	Direct
Maximaler Verbrauch	max 36 W
Merkmale LED	LED SMD SAMSUNG
CCT LED	4000 K
Dauer LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Lichtstrahlwinkel	105°
Lichtstrahlfluss	5200 lm
Nützlicher Lichtstrom	3450 lm
Photobiologisches Risiko	1