


Allgemeine Information

Innen - Wandleuchten



Ean	8021696158242
Artikel	NORDIK AP2
Installation	Wandleuchten
Garantie	5 years
Bruttogewicht	1.16 kg
Volumen	0.011109 m³

Technische Information

Nettogewicht	0.63 kg
Isolationsklasse	I
Schutzindex	IP20
Einhaltung	CE
Betriebstemperatur	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Leistung	100-240 V AC 50/60 Hz
Energieversorgung	In-built, included Replaceable (by qualified operators only), electronic

Quellinfo

Integrierte Quelle	Light bulb (not included), Integrated LED module
Austauschbare Quelle	Replaceable (LED: by qualified operators only)
Leistung	E14/LED max 1 x 40W / 1.5 W
Emissionen	Diffuse + Direct
Maximaler Verbrauch	max 40W / LED 1.5 W
Merkmale LED	LED SMD BRIDGELUX
CCT LED	3000 K
Dauer LED (t. 25°C)	20000 h
CRI	> 90
SDCM	3
Lichtstrahlwinkel	23°
Lichtstrahlfluss	100 lm
Nützlicher Lichtstrom	80 lm
Photobiologisches Risiko	2
Glühbirne empfehlen	101200 E14 SFERA 4W 3000K CRI80 TRASP