

## Allgemeine Information


## Innen - Deckenleuchten



|                      |                                |
|----------------------|--------------------------------|
| <b>Ean</b>           | 8021696365022                  |
| <b>Artikel</b>       | OZ PL D100 ON-OFF OTTONE 3000K |
| <b>Installation</b>  | Deckenleuchten                 |
| <b>Garantie</b>      | 5 years                        |
| <b>Bruttogewicht</b> | 6.4 kg                         |
| <b>Volumen</b>       | 0.097344 m <sup>3</sup>        |

## Technische Information

|                           |  |
|---------------------------|--|
| <b>Nettogewicht</b>       | 3 kg   |
| <b>Isolationsklasse</b>   | II   |
| <b>Schutzindex</b>        | IP20   |
| <b>Einhaltung</b>         | CE   |
| <b>Betriebstemperatur</b> | 0° ~ +40 °C  |
| <b>Dimmer</b>             | Non-dimmable, On-Off   |
| <b>Leistung</b>           | 220-240 V AC 50/60 Hz  |
| <b>Energieversorgung</b>  | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Quellinfo

|                                 |                       |
|---------------------------------|-----------------------|
| <b>Integrierte Quelle</b>       | Integrated LED module |
| <b>Austauschbare Quelle</b>     | No                    |
| <b>Leistung</b>                 | 75 W                  |
| <b>Emissionen</b>               | Diffuse               |
| <b>Maximaler Verbrauch</b>      | max 75 W              |
| <b>Merkmale LED</b>             | LED SMD               |
| <b>CCT LED</b>                  | 3000 K                |
| <b>Dauer LED (t. 25°C)</b>      | 30000 h               |
| <b>CRI</b>                      | > 90                  |
| <b>SDCM</b>                     | 3                     |
| <b>Lichtstrahlwinkel</b>        | -                     |
| <b>Lichtstrahlfluss</b>         | 8300 lm               |
| <b>Nützlicher Lichtstrom</b>    | 4010 lm               |
| <b>Photobiologisches Risiko</b> | EXEMPT                |