

## Allgemeine Information

## Innen - Wandleuchten



|               |                       |
|---------------|-----------------------|
| Ean           | 8021696142272         |
| Artikel       | RIFLESSO AP D42 CROMO |
| Installation  | Wandleuchten          |
| Garantie      | 5 years               |
| Bruttogewicht | 0.85 kg               |
| Volumen       | 0.00264 m³            |

## Technische Information

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Nettogewicht       | 0.6 kg                                                                         |
| Isolationsklasse   | I                                                                              |
| Schutzindex        | IP54                                                                           |
| Einhaltung         | CE                                                                             |
| Betriebstemperatur | 0° ~ +40 °C                                                                    |
| Dimmer             | Non-dimmable, On-Off                                                           |
| Leistung           | 220-240 V AC 50/60 Hz                                                          |
| Energieversorgung  | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Quellinfo

|                          |                                           |
|--------------------------|-------------------------------------------|
| Integrierte Quelle       | Integrated LED module                     |
| Austauschbare Quelle     | Replaceable (by qualified operators only) |
| Leistung                 | LED 10 W                                  |
| Emissionen               | Diffuse                                   |
| Maximaler Verbrauch      | max 10 W                                  |
| Merkmale LED             | LED SMD                                   |
| CCT LED                  | 3000 K                                    |
| Dauer LED (t. 25°C)      | 20000 h                                   |
| CRI                      | > 90                                      |
| SDCM                     | 3                                         |
| Lichtstrahlfluss         | 1250 lm                                   |
| Nützlicher Lichtstrom    | 650 lm                                    |
| Photobiologisches Risiko | 1                                         |