

Allgemeine Information


Aussen - Strahler



Ean	8021696248387
Artikel	STARLIGHT PR 10.0W 3000K
Installation	Strahler
Garantie	5 years
Bruttogewicht	1.23 kg
Volumen	0.001872 m³

Technische Information

Nettogewicht	0.95 kg
Isolationsklasse	III
Schutzindex	IP68
Einhaltung	CE
Betriebstemperatur	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Leistung	24 V DC
Energieversorgung	Required, remoted, not included NO
Lastwiderstand	IK07
Zubehör nicht inklusive	Glare shielding cover, Ground fixing spike, Remote on-off driver



Quellinfo

Integrierte Quelle	Integrated LED module
Austauschbare Quelle	Replaceable (by qualified operators only)
Leistung	10 W
Emissionen	Direct
Maximaler Verbrauch	max 10 W
Merkmale LED	LED COB BRIDGELUX
CCT LED	3000 K
Dauer LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Lichtstrahlwinkel	30°
Lichtstrahlfluss	1050 lm
Nützlicher Lichtstrom	770 lm
Photobiologisches Risiko	1