



## Allgemeine Information

### Technisch - Systeme

|               |                       |
|---------------|-----------------------|
| Ean           | 8021696270180         |
| Artikel       | STEEL ACCENT 3000K WH |
| Installation  | Systeme               |
| Garantie      | 5 years               |
| Bruttogewicht | 2.52 kg               |
| Volumen       | 0.021357 m³           |

## Technische Information

|                         |                                                                                       |
|-------------------------|---------------------------------------------------------------------------------------|
| Nettogewicht            | 1.98 kg                                                                               |
| Isolationsklasse        | I                                                                                     |
| Schutzindex             | IP20                                                                                  |
| Einhaltung              | CE                                                                                    |
| Betriebstemperatur      | 0° ~ +40 °C                                                                           |
| Dimmer                  | Non-dimmable, On-Off                                                                  |
| Leistung                | 220-240 V AC 50/60 Hz                                                                 |
| Energieversorgung       | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, osram |
| Zubehör nicht inklusive | Mounting kit (suspension or surface), Straight<br>continuous linear connector         |

## Quellinfo

|                       |                                           |
|-----------------------|-------------------------------------------|
| Integrierte Quelle    | Integrated LED module                     |
| Austauschbare Quelle  | Replaceable (by qualified operators only) |
| Leistung              | 36 W                                      |
| Emissionen            | Direct + Indirect                         |
| Maximaler Verbrauch   | max 36 W                                  |
| Merkmale LED          | LED SMD SAMSUNG                           |
| CCT LED               | 3000 K                                    |
| Dauer LED (t. 25°C)   | 50000 h                                   |
| CRI                   | > 90                                      |
| SDCM                  | 3                                         |
| Lichtstrahlwinkel     | 60+110°                                   |
| UGR Maximal           | < 16                                      |
| Lichtstrahlfluss      | 3600 lm                                   |
| Nützlicher Lichtstrom | 3110 lm                                   |