

Allgemeine Information

Technisch - Systeme

Ean	8021696270203
Artikel	STEEL SP2 D35 BI-EMISSION WIDE 4000K BIANCO
Installation	Systeme
Garantie	5 years
Bruttogewicht	2.52 kg
Volumen	0.011172 m ³

Technische Information

Nettogewicht	1.99 kg
Isolationsklasse	I
Schutzindex	IP20
Einhaltung	CE
Betriebstemperatur	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Leistung	220-240 V AC 50/60 Hz
Energieversorgung	In-built, included Replaceable (by qualified operators only), electronic, osram inventronics
Zubehör nicht inklusive	Mounting kit (suspension or surface), Straight continuous linear connector



Quellinfo

Integrierte Quelle	Integrated LED module
Austauschbare Quelle	Replaceable (by qualified operators only)
Leistung	36 W
Emissionen	Direct + Indirect
Maximaler Verbrauch	max 36 W
Merkmale LED	LED SMD SAMSUNG
CCT LED	4000 K
Dauer LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Lichtstrahlwinkel	70+110°
UGR Maximal	< 19
Lichtstrahlfluss	4500 lm
Nützlicher Lichtstrom	2900 lm
Photobiologisches Risiko	EXEMPT