

## Allgemeine Information


## Aussen - Wandleuchten



|               |                       |
|---------------|-----------------------|
| Ean           | 8021696269139         |
| Artikel       | STYLE AP BIANCO 3000K |
| Installation  | Wandleuchten          |
| Garantie      | 5 years               |
| Bruttogewicht | 0.48 kg               |
| Volumen       | 0.00176 m³            |

## Technische Information

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Nettogewicht       | 0.39 kg                                                                        |
| Isolationsklasse   | I                                                                              |
| Schutzindex        | IP54                                                                           |
| Einhaltung         | CE                                                                             |
| Betriebstemperatur | -15° ~ +45 °C                                                                  |
| Dimmer             | Non-dimmable, On-Off                                                           |
| Leistung           | 100-240 V AC 50/60 Hz                                                          |
| Energieversorgung  | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |
| Lastwiderstand     | IK06                                                                           |



## Quellinfo

|                       |                       |
|-----------------------|-----------------------|
| Integrierte Quelle    | Integrated LED module |
| Austauschbare Quelle  | No                    |
| Leistung              | 8,5 W                 |
| Emissionen            | Direct                |
| Maximaler Verbrauch   | max 8,5 W             |
| Merkmale LED          | LED SMD               |
| CCT LED               | 3000 K                |
| Dauer LED (t. 25°C)   | 30000 h               |
| CRI                   | > 90                  |
| SDCM                  | 3                     |
| Lichtstrahlwinkel     | 120°                  |
| Lichtstrahlfluss      | 950 lm                |
| Nützlicher Lichtstrom | 740 lm                |