



## Allgemeine Information

### Aussen - Stehleuchten

<b>Ean</b>	8021696187327
<b>Artikel</b>	TITANO PT H74 4000K
<b>Installation</b>	Stehleuchten
<b>Garantie</b>	5 years
<b>Bruttogewicht</b>	11.52 kg
<b>Volumen</b>	0.05395 m <sup>3</sup>

## Technische Information

<b>Nettogewicht</b>	9.22 kg
<b>Isolationsklasse</b>	II
<b>Schutzindex</b>	IP55
<b>Einhaltung</b>	CE
<b>Betriebstemperatur</b>	-15° ~ +45 °C
<b>Dimmer</b>	Non-dimmable, On-Off
<b>Leistung</b>	100-240 V AC 50/60 Hz
<b>Energieversorgung</b>	In-built, included Replaceable (by qualified operators only), electronic

## Quellinfo

<b>Integrierte Quelle</b>	Integrated LED module
<b>Austauschbare Quelle</b>	Replaceable (by qualified operators only)
<b>Leistung</b>	8,5 W
<b>Emissionen</b>	Direct Asymmetrical
<b>Maximaler Verbrauch</b>	max 8,5 W
<b>Merkmale LED</b>	LED COB
<b>CCT LED</b>	4000 K
<b>Dauer LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 90
<b>SDCM</b>	3
<b>Lichtstrahlwinkel</b>	-
<b>Lichtstrahlfluss</b>	580 lm
<b>Nützlicher Lichtstrom</b>	220 lm