



## General info

### Indoor - Floor lamps

|              |                                 |
|--------------|---------------------------------|
| Ean          | 8021696345307                   |
| Item         | COMFORT-2 PT BIANCO 2700K-5700K |
| Installation | Floor lamps                     |
| Warranty     | 5 years                         |
| Gross weight | 22.7 kg                         |
| Volume       | 0.070173 m <sup>3</sup>         |

## Technical info

|                       |                                                       |
|-----------------------|-------------------------------------------------------|
| Net weight            | 19.5 kg                                               |
| Insulation class      | I                                                     |
| Protection index      | IP20                                                  |
| Compliance            | CE                                                    |
| Operating temperature | 0° ~ +40 °C                                           |
| Dimmer                | 1, Touch dimmer, PIR Motion Sensor, Luminosity Sensor |
| Power output          | 220-240 V AC 50/60 Hz                                 |
| Power supply          | In-built, included<br>NO, electronic                  |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Repleaceable source    | No                    |
| Power                  | 76 W                  |
| Emission               | Direct + Indirect     |
| Max consupcion         | max 76 W              |
| Features LED           | LED SMD               |
| CCT LED                | 2700-5700 K           |
| Duration LED (t. 25°C) | 50000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam             | 75+140°               |
| UGR Maximum            | < 16                  |
| Light beam flux        | 7600 lm               |
| Useful light flux      | 6200 lm               |
| Photobiological risk   | 1                     |
| Standby power          | < 0.50 W              |