


## General info

## Technical - Systems



|                     |                            |
|---------------------|----------------------------|
| <b>Ean</b>          | 8021696369907              |
| <b>Item</b>         | DEVA ACCENT 05W 4000K NERO |
| <b>Installation</b> | Systems                    |
| <b>Warranty</b>     | 5 years                    |
| <b>Gross weight</b> | 0.08 kg                    |
| <b>Volume</b>       | 0.0006 m <sup>3</sup>      |

## Technical info

|                                 |                                 |
|---------------------------------|---------------------------------|
| <b>Net weight</b>               | 0.07 kg                         |
| <b>Insulation class</b>         | III                             |
| <b>Protection index</b>         | IP20                            |
| <b>Compliance</b>               | CE                              |
| <b>Operating temperature</b>    | 0° ~ +40 °C [DO NOT COVER]      |
| <b>Dimmer</b>                   | Non-dimmable, On-Off            |
| <b>Power output</b>             | 24 V DC                         |
| <b>Power supply</b>             | Required, remoted, not included |
| <b>Accessories not included</b> | Deva profile                    |

## Source info

|                               |   |
|-------------------------------|---|
| <b>Integrated source</b>      | Integrated LED module                     |
| <b>Replaceable source</b>     | Replaceable (by qualified operators only) |
| <b>Power</b>                  | 5 W                                       |
| <b>Emission</b>               | Direct                                    |
| <b>Max consumption</b>        | max 5 W                                   |
| <b>Features LED</b>           | LED SMD                                   |
| <b>CCT LED</b>                | 4000 K                                    |
| <b>Duration LED (t. 25°C)</b> | 30000 h                                   |
| <b>CRI</b>                    | > 90                                      |
| <b>SDCM</b>                   | 3   |
| <b>Light beam</b>             | 34°                                       |
| <b>Light beam flux</b>        | 470 lm                                    |
| <b>Useful light flux</b>      | 380 lm                                    |
| <b>Photobiological risk</b>   | 1   |