ideal lux.



Deva

General info

Technical - Systems

| Ean | 8021696332734 |
|--------------|------------------------|
| Item | DEVA ACCENT 10W BK |
| Installation | Systems |
| Warranty | 5 years |
| Gross weight | 0.15 kg |
| Volume | 0.00048 m ³ |

Technical info

| | 241 | | |
|-------------|-----|---------|----------|
| 8 8 8 | | • 8 •X• | 100 |
| 0 | 196 | • | 11 11 |

| Net weight |
|--------------------------|
| Insulation class |
| Protection index |
| Compliance |
| Operating temperature |
| Dimmer |
| Power output |
| Power supply |
| Accessories not included |

0.14 kg III IP20 CE 0° ~ +40 °C [DO NOT COVER] Non-dimmable, On-Off 24 V DC Required, remoted, not included Deva profile

Source info

| Integrated source | Integrated LED module | |
|------------------------|---|--|
| Repleaceable source | Replaceable (by qualified operators only) | |
| Power | 10 W | |
| Emission | Direct | |
| Max consuption | max 10 W | |
| Features LED | LED SMD | |
| CCT LED | 3000 K | |
| Duration LED (t. 25°c) | 30000 h | |
| CRI | > 90 | |
| SDCM | 3 | |
| Light beam | 34° | |
| Light beam flux | 900 lm | |
| Useful light flux | 730 lm | |
| Photobiological risk | EXEMPT | |