ideal lux.



Diesis

General info

Indoor - Suspensions

| Ean | 8021696279794 |
|--------------|------------------|
| Item | DIESIS SP OTTONE |
| Installation | Suspensions |
| Warranty | 5 years |
| Gross weight | 0.58 kg |
| Volume | 0.00507 m³ |

90 2430 255 00 60

| 00 | hh | | Into |
|----|----|-------|------|
| | | 1 7 4 | info |
| | | | |

| Net weight | 0.45 kg |
|-----------------------|---|
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included |
| | Replaceable (by qualified operators only), electronic |

Source info

| Integrated source | Integrated LED module |
|------------------------|---|
| Repleaceable source | Replaceable (by qualified operators only) |
| Power | LED 7 W |
| Emission | Direct |
| Max consuption | max 7 W |
| Features LED | LED COB |
| CCT LED | 3000 K |
| Duration LED (t. 25°c) | 20000 h |
| CRI | > 95 |
| SDCM | 3 |
| Light beam flux | 560 lm |
| Useful light flux | 400 lm |
| Photobiological risk | 1 |