



## General info

### Technical - Systems

|                     |                                |
|---------------------|--------------------------------|
| <b>Ean</b>          | 8021696257686                  |
| <b>Item</b>         | EGO ACCENT 13W 3000K ON-OFF NE |
| <b>Installation</b> | Systems                        |
| <b>Warranty</b>     | 5 years                        |
| <b>Gross weight</b> | 0.42 kg                        |
| <b>Volume</b>       | 0.001085 m <sup>3</sup>        |

## Technical info

|                              |              |
|------------------------------|--------------|
| <b>Net weight</b>            | 0.33 kg      |
| <b>Insulation class</b>      | III          |
| <b>Protection index</b>      | IP20         |
| <b>Compliance</b>            | -            |
| <b>Operating temperature</b> | -            |
| <b>Dimmer</b>                | Non-dimmable |
| <b>Power output</b>          | 48 V DC      |
| <b>Power supply</b>          | -            |

## Source info

|                               |               |
|-------------------------------|---------------|
| <b>Integrated source</b>      | -             |
| <b>Replaceable source</b>     | No            |
| <b>Power</b>                  | 13 W          |
| <b>Emission</b>               | -             |
| <b>Max consumption</b>        | -             |
| <b>Features LED</b>           | LED SMD OSRAM |
| <b>CCT LED</b>                | 3000 K        |
| <b>Duration LED (t. 25°C)</b> | 50 h          |
| <b>CRI</b>                    | > 90          |
| <b>SDCM</b>                   | 3             |
| <b>Light beam</b>             | 35°           |
| <b>UGR Maximum</b>            | < 19          |
| <b>Light beam flux</b>        | 1400 lm       |
| <b>Useful light flux</b>      | -             |