



## General info

### Technical - Systems

|              |                                     |
|--------------|-------------------------------------|
| Ean          | 8021696303574                       |
| Item         | EGO PENDANT TUBE 12W 3000K 1-10V BK |
| Installation | Systems                             |
| Warranty     | 5 years                             |
| Gross weight | 0.75 kg                             |
| Volume       | 0.00248 m <sup>3</sup>              |

## Technical info

|                          |                                       |
|--------------------------|---------------------------------------|
| Net weight               | 0.55 kg                               |
| Insulation class         | III                                   |
| Protection index         | IP20                                  |
| Compliance               | CE                                    |
| Operating temperature    | 0° ~ +40 °C                           |
| Dimmer                   | 1, 1-10V                              |
| Power output             | 48 V DC                               |
| Power supply             | Required, remoted, not included<br>NO |
| Accessories not included | Ego profile                           |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 12 W                                      |
| Emission               | Direct                                    |
| Max consupcion         | max 12 W                                  |
| Features LED           | LED COB CITIZEN                           |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 30°                                       |
| UGR Maximum            | < 19                                      |
| Light beam flux        | 1150 lm                                   |
| Useful light flux      | 820 lm                                    |
| Photobiological risk   | 1                                         |
| Standby power          | < 0.50 W                                  |