# ideal lux.

# Fluo

### General info

#### **Technical - Systems**

| Ean          | 8021696192666                  |
|--------------|--------------------------------|
| Item         | FLUO BI-EMISSION 1200 3000K WH |
| Installation | Systems                        |
| Warranty     | 5 years                        |
| Gross weight | 4.89 kg                        |
| Volume       | 0.018383 m³                    |

## Technical info

| Net weight               | 2.89 kg  |
|--------------------------|--|
| Insulation class         | I  |
| Protection index         | IP20   |
| Compliance               | CE   |
| Operating temperature    | 0° ~ +40 °C  |
| Dimmer                   | Non-dimmable, On-Off   |
| Power output             | 220-240 V AC 50/60 Hz  |
| Power supply             | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic |
| Accessories not included | Mounting kit (suspension), Dimmable drivers kit,   |

Structure connector

1205 **50** 

#### Source info

| Integrated source      | Integrated LED module |
|------------------------|-----------------------|
| Repleaceable source    | No                    |
| Power                  | 40 W                  |
| Emission               | Direct + Indirect     |
| Max consuption         | max 40 W              |
| Features LED           | LED SMD SAMSUNG       |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°c) | 50000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam             | 105+105°              |
| Light beam flux        | 5500 lm               |
| Useful light flux      | 3820 lm               |
| Photobiological risk   | 1                     |