
ideal lux.





Fox

General info

Technical - Spotlights and Tracks

| Ean | 8021696302560 |
|--------------|--|
| Item | FOX TR 3-PHASE 15W CRI90 3000K 1-10V WH |
| Installation | Spotlights and Tracks |
| Warranty | 5 years |
| Gross weight | 0.68 kg |
| Volume | 0.00408 m ³ |

Technical info

| Net weight | 0.56 kg |
|--------------------------|---------------------------------|
| Insulation class | П |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | 1, 1-10V |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included |
| | NO, electronic |
| Accessories not included | Link 3-phase 1-10V/DALI profile |

Source info

| Integrat |
|----------|
| Replace |
| 15 W |
| Direct |
| max 15 |
| LED CO |
| 3000 K |
| 50000 ł |
| > 90 |
| 3 |
| 41° |
| 1600 lm |
| 1350 lm |
| 1 |
| < 0.50 |
| |

| Integrated LED module |
|---|
| Replaceable (by qualified operators only) |
| 15 W |
| Direct |
| max 15 W |
| LED COB BRIDGELUX |
| 3000 K |
| 50000 h |
| > 90 |
| 3 |
| 41° |
| 1600 lm |
| 1350 lm |
| 1 |
| < 0.50 W |