



General info

Technical - Spotlights and Tracks

| | |
|--------------|--|
| Ean | 8021696302577 |
| Item | FOX TR 3-PHASE 15W CRI90 3000K DALI BK |
| Installation | Spotlights and Tracks |
| Warranty | 5 years |
| Gross weight | 0.68 kg |
| Volume | 0.0042 m ³ |

Technical info

| | |
|--------------------------|--------------------------------------|
| Net weight | 0.56 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | 1, DALI |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included NO, electronic |
| Accessories not included | Link 3-phase 1-10V/DALI profile |

Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 15 W |
| Emission | Direct |
| Max consupcion | max 15 W |
| Features LED | LED COB BRIDGELUX |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 41° |
| Light beam flux | 1600 lm |
| Useful light flux | 1350 lm |
| Photobiological risk | 1 |
| Standby power | < 0.50 W |