



## General info

### Technical - Spotlights and Tracks

|              |                                         |
|--------------|-----------------------------------------|
| Ean          | 8021696340869                           |
| Item         | FOX TR 3-PHASE 08W CRI90 4000K 1-10V WH |
| Installation | Spotlights and Tracks                   |
| Warranty     | 5 years                                 |
| Gross weight | 0.55 kg                                 |
| Volume       | 0.0024 m <sup>3</sup>                   |

## Technical info

|                          |                                      |
|--------------------------|--------------------------------------|
| Net weight               | 0.5 kg                               |
| Insulation class         | II                                   |
| Protection index         | IP20                                 |
| Compliance               | CE                                   |
| Operating temperature    | 0° ~ +40 °C                          |
| Dimmer                   | 1, 1-10V                             |
| Power output             | 220-240 V AC 50/60 Hz                |
| Power supply             | In-built, included<br>NO, electronic |
| Accessories not included | Link 3-phase 1-10V/DALI profile      |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 8 W                                       |
| Emission               | Direct                                    |
| Max consupcion         | max 8 W                                   |
| Features LED           | LED COB BRIDGELUX                         |
| CCT LED                | 4000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 41°                                       |
| Light beam flux        | 1050 lm                                   |
| Useful light flux      | 760 lm                                    |
| Photobiological risk   | 1                                         |
| Standby power          | < 0.50 W                                  |