
ideal lux.





Fox

General info

Technical - Spotlights and Tracks

Ean	8021696340968
Item	FOX TR 3-PHASE 25W CRI90 4000K 1-10V WH
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.87 kg
Volume	0.00378 m³

Technical info

Net weight	0.78 kg
Insulation class	П
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	1, 1-10V
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	NO, electronic
Accessories not included	Link 3-phase 1-10V/DALI profile

Source info

Integrated source	Integr
Repleaceable source	Repla
Power	25 W
Emission	Direct
Max consuption	max 2
Features LED	LED (
CCT LED	4000
Duration LED (t. 25°c)	50000
CRI	> 90
SDCM	3
Light beam	35°
Light beam flux	3050
Useful light flux	2310
Photobiological risk	1
Standby power	< 0.5

Integrated LED module
Replaceable (by qualified operators only)
25 W
Direct
max 25 W
LED COB BRIDGELUX
4000 K
50000 h
> 90
3
35°
3050 lm
2310 lm
1
< 0.50 W