



## General info

### Technical - Recessed lights

|                     |                                 |
|---------------------|---------------------------------|
| <b>Ean</b>          | 8021696349084                   |
| <b>Item</b>         | GAME TRIM ROUND 05W 3000K BI OR |
| <b>Installation</b> | Recessed lights                 |
| <b>Warranty</b>     | 5 years                         |
| <b>Gross weight</b> | 0.22 kg                         |
| <b>Volume</b>       | 0.000912 m <sup>3</sup>         |

## Technical info

|                              |              |
|------------------------------|--------------|
| <b>Net weight</b>            | 0.2 kg       |
| <b>Insulation class</b>      | II           |
| <b>Protection index</b>      | IP20         |
| <b>Compliance</b>            | -            |
| <b>Operating temperature</b> | -            |
| <b>Dimmer</b>                | Non-dimmable |
| <b>Power output</b>          | 220-240 V AC |
| <b>Power supply</b>          | -            |

## Source info

|                               |              |
|-------------------------------|--------------|
| <b>Integrated source</b>      | -            |
| <b>Replaceable source</b>     | No           |
| <b>Power</b>                  | 5,5 W        |
| <b>Emission</b>               | -            |
| <b>Max consumption</b>        | -            |
| <b>Features LED</b>           | LED COB CREE |
| <b>CCT LED</b>                | 3000 K       |
| <b>Duration LED (t. 25°C)</b> | 50 h         |
| <b>CRI</b>                    | > 90         |
| <b>SDCM</b>                   | 3            |
| <b>Light beam</b>             | 36°          |
| <b>UGR Maximum</b>            | < 19         |
| <b>Light beam flux</b>        | 650 lm       |
| <b>Useful light flux</b>      | -            |