


General info

Technical - Recessed lights



| | |
|---------------------|------------------------------------|
| Ean | 8021696249711 |
| Item | LED PANEL FI 60X60 40W CRI80 3000K |
| Installation | Recessed lights |
| Warranty | 5 years |
| Gross weight | 2.7 kg |
| Volume | 0.018428 m ³ |

Technical info

| | |
|---------------------------------|---|
| Net weight | 2.2 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | Separate, included Replaceable (by qualified operators only), electronic |
| Accessories not included | Dimmable driver, Mounting kit (Suspension kit, Surface kit, Plasterboard recessed frame) |

Source info

| | |
|-------------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 40 W |
| Emission | Direct |
| Max consumption | max 40 W |
| Features LED | LED SMD |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 30000 h |
| CRI | > 80 |
| SDCM | 3 |
| Light beam | 90° |
| UGR Maximum | < 19 |
| Light beam flux | 6700 lm |
| Useful light flux | 4150 lm |
| Photobiological risk | EXEMPT |