


General info

Technical - Systems

| | |
|--------------|--------------------|
| Ean | 8021696271187 |
| Item | OFFICE SP 3000K BK |
| Installation | Systems |
| Warranty | 5 years |
| Gross weight | 1.86 kg |
| Volume | 0.004128 m³ |

Technical info

| | |
|-----------------------|--|
| Net weight | 1.82 kg |
| Insulation class | I |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic |
| Load resistance | IK06 |



Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 30 W |
| Emission | Direct |
| Max consupcion | max 30 W |
| Features LED | LED SMD |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 37° |
| UGR Maximum | < 16 |
| Light beam flux | 3550 lm |
| Useful light flux | 2270 lm |