



## General info

### Indoor - Suspensions

|                     |   |
|---------------------|---|
| <b>Ean</b>          | 8021696304380                             |
| <b>Item</b>         | ORACLE SLIM SP D050 ROUND 4000K ON-OFF NE |
| <b>Installation</b> | Suspensions                               |
| <b>Warranty</b>     | 5 years                                   |
| <b>Gross weight</b> | 2.37 kg                                   |
| <b>Volume</b>       | 0.03025 m <sup>3</sup>                    |

## Technical info

|                              |              |
|------------------------------|--------------|
| <b>Net weight</b>            | 1.1 kg       |
| <b>Insulation class</b>      | II           |
| <b>Protection index</b>      | IP20         |
| <b>Compliance</b>            | -            |
| <b>Operating temperature</b> | -            |
| <b>Dimmer</b>                | Non-dimmable |
| <b>Power output</b>          | 220-240 V AC |
| <b>Power supply</b>          | -            |

## Source info

|                               |         |
|-------------------------------|---------|
| <b>Integrated source</b>      | -       |
| <b>Replaceable source</b>     | No      |
| <b>Power</b>                  | 29 W    |
| <b>Emission</b>               | -       |
| <b>Max consumption</b>        | -       |
| <b>Features LED</b>           | LED SMD |
| <b>CCT LED</b>                | 4000 K  |
| <b>Duration LED (t. 25°C)</b> | 50 h    |
| <b>CRI</b>                    | > 90    |
| <b>SDCM</b>                   | 3       |
| <b>Light beam</b>             | 115°    |
| <b>Light beam flux</b>        | 3550 lm |
| <b>Useful light flux</b>      | -       |