


## General info

## Indoor - Wall lamps



|              |                    |
|--------------|--------------------|
| Ean          | 8021696142579      |
| Item         | PAGE AP ROUND NERO |
| Installation | Wall lamps         |
| Warranty     | 5 years            |
| Gross weight | 0.46 kg            |
| Volume       | 0.002535 m³        |

## Technical info



|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.32 kg                                                                        |
| Insulation class      | I                                                                              |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | LED 3 W               |
| Emission               | Direct                |
| Max consupcion         | max 3 W               |
| Features LED           | LED SMD CREE          |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 30000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam flux        | 240 lm                |
| Useful light flux      | 180 lm                |