


## General info

## Technical - Recessed lights



|              |                                   |
|--------------|-----------------------------------|
| Ean          | 8021696322971                     |
| Item         | QUARK FI 9.0W ADJUSTABLE 3000K BK |
| Installation | Recessed lights                   |
| Warranty     | 5 years                           |
| Gross weight | 0.25 kg                           |
| Volume       | 0.000675 m³                       |

## Technical info



|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.21 kg                                                                        |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | Separate, included<br>Replaceable (by qualified operators only),<br>electronic |

## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | 9 W                   |
| Emission               | Direct                |
| Max consupcion         | max 9 W               |
| Features LED           | LED COB               |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 50000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam             | 25°                   |
| Light beam flux        | 950 lm                |
| Useful light flux      | 630 lm                |
| Photobiological risk   | EXEMPT                |