
# ideal lux.





# Smile

### General info

#### **Technical - Spotlights and Tracks**

Ean	8021696189758
Item	SMILE TR 3-PHASE 15W CRI80 36° 3000K WH
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.61 kg
Volume	-

## **Technical info**

Net weight	0.61 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Load resistance	IK06
Accessories not included	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

#### Source info

Integrated source	Inte
Repleaceable source	Rep
Power	15 V
Emission	Dire
Max consuption	max
Features LED	LED
CCT LED	300
Duration LED (t. 25°c)	500
CRI	> 80
SDCM	3
Light beam	36°
Light beam flux	205
Useful light flux	178

Integrated LED module Replaceable (by qualified operators only) 15 W Direct max 15 W LED COB PHILIPS 3000 K 50000 h > 80 3 36° 2050 lm 1780 lm