
ideal lux.





Smile

General info

Technical - Spotlights and Tracks

Ean	8021696189956
Item	SMILE TR 3-PHASE 15W CRI80 50° 4000K WH
Installation	Spotlights and Tracks
Warranty	5 years
Gross weight	0.61 kg
Volume	_

Technical info

Net weight	0.61 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Load resistance	IK06
Accessories not included	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

Source info

Integrated source	Integrated
Repleaceable source	Replaceat
Power	15 W
Emission	Direct
Max consuption	max 15 W
Features LED	LED COB
CCT LED	4000 K
Duration LED (t. 25°c)	50000 h
CRI	> 80
SDCM	3
Light beam	50°
Light beam flux	2250 lm
Useful light flux	1870 lm

Integrated LED module Replaceable (by qualified operators only) 15 W Direct max 15 W LED COB PHILIPS 4000 K 50000 h > 80 3 50° 2250 lm