
# ideal lux.





# Smile

### General info

#### **Technical - Spotlights and Tracks**

| Ean          | 8021696189598                              |
|--------------|--|
| Item         | SMILE TR 3-PHASE 15W CRI90 24° 3000K<br>WH |
| Installation | Spotlights and Tracks                      |
| Warranty     | 5 years                                    |
| Gross weight | 0.61 kg                                    |
| Volume       | -  |

## **Technical info**

| Net weight               | 0.61 kg  |
|--------------------------|--|
| Insulation class         | II   |
| Protection index         | IP20   |
| Compliance               | CE   |
| Operating temperature    | 0° ~ +40 °C  |
| Dimmer                   | Non-dimmable, On-Off   |
| Power output             | 220-240 V AC 50/60 Hz  |
| Power supply             | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic             |
| Load resistance          | IK06   |
| Accessories not included | Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile |

#### Source info

| Integrated source      | Integrated LED module                     |
|------------------------|---|
| Repleaceable source    | Replaceable (by qualified operators only) |
| Power                  | 15 W                                      |
| Emission               | Direct                                    |
| Max consuption         | max 15 W                                  |
| Features LED           | LED COB PHILIPS                           |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°c) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3   |
| Light beam             | 24°                                       |
| Light beam flux        | 1700 lm                                   |
| Useful light flux      | 1430 lm                                   |