
ideal lux.





Smile

General info

Technical - Spotlights and Tracks

Ean	8021696189673	
Item	SMILE TR 3-PHASE 20W CRI80 24° 4000K WH	
Installation	Spotlights and Tracks	
Warranty	5 years	
Gross weight	0.87 kg	
Volume	-	

Technical info

Net weight	0.87 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Load resistance	IK06
Accessories not included	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

Source info

Integrated source	Integ
Repleaceable source	Repla
Power	20 W
Emission	Direc
Max consuption	max
Features LED	LED
CCT LED	4000
Duration LED (t. 25°c)	5000
CRI	> 80
SDCM	3
Light beam	24°
Light beam flux	3150
Useful light flux	2660

Integrated LED module Replaceable (by qualified operators only) 20 W Direct max 20 W LED COB PHILIPS 4000 K 50000 h > 80 3 24° 3150 lm 2660 lm