



General info

Technical - Systems

| | |
|--------------|-------------------------|
| Ean | 8021696270173 |
| Item | STEEL ACCENT 4000K BK |
| Installation | Systems |
| Warranty | 5 years |
| Gross weight | 2.52 kg |
| Volume | 0.011074 m ³ |

Technical info

| | |
|--------------------------|---|
| Net weight | 1.98 kg |
| Insulation class | I |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Dimmer | Non-dimmable, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic, osram |
| Accessories not included | Mounting kit (suspension or surface), Straight continuous linear connector |

Source info

| | |
|------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 36 W |
| Emission | Direct + Indirect |
| Max consupcion | max 36 W |
| Features LED | LED SMD SAMSUNG |
| CCT LED | 4000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 60+110° |
| UGR Maximum | < 16 |
| Light beam flux | 3700 lm |
| Useful light flux | 3200 lm |