## General info

**Technical - Systems**

| | |
|---|---|
| **Ean** | 8021696270203 |
| **Item** | STEEL WIDE 4000K WH |
| **Installation** | Systems |
| **Warranty** | 5 years |
| **Gross weight** | 2.52 kg |
| **Volume** | 0.011074 m³ |

## Technical info

| | |
|---|---|
| **Net weight** | 1.99 kg |
| **Insulation class** | I |
| **Protection index** | IP20 |
| **Compliance** | CE |
| **Operating temperature** | 0° ~ +40 °C |
| **Dimmer** | Non-dimmable, On-Off |
| **Power output** | 220-240 V AC 50/60 Hz |
| **Power supply** | In-built, included |
| | Replaceable (by qualified operators only), electronic, osram |
| **Accessories not included** | Mounting kit (suspension or surface), Straight continuous linear connector |

## Source info

| | |
|---|---|
| **Integrated source** | Integrated LED module |
| **Repleaceable source** | Replaceable (by qualified operators only) |
| **Power** | 36 W |
| **Emission** | Direct + Indirect |
| **Max consuption** | max 36 W |
| **Features LED** | LED SMD SAMSUNG |
| **CCT LED** | 4000 K |
| **Duration LED (t. 25°c)** | 50000 h |
| **CRI** | > 90 |
| **SDCM** | 3 |
| **Light beam** | 70+110° |
| **UGR Maximum** | < 19 |
| **Light beam flux** | 4500 lm |
| **Useful light flux** | 2900 lm |

1070  35