

## General info


## Indoor - Ceiling lamps



|              |                               |
|--------------|-------------------------------|
| Ean          | 8021696138640                 |
| Item         | UNIVERSAL PL D22 SQUARE 3000K |
| Installation | Ceiling lamps                 |
| Warranty     | 5 years                       |
| Gross weight | 0.82 kg                       |
| Volume       | 0.002432 m³                   |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.71 kg                                                                        |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Source info

|                        |                       |
|------------------------|-----------------------|
| Integrated source      | Integrated LED module |
| Replaceable source     | No                    |
| Power                  | 17 W                  |
| Emission               | Direct                |
| Max consupcion         | max 17 W              |
| Features LED           | LED SMD               |
| CCT LED                | 3000 K                |
| Duration LED (t. 25°C) | 30000 h               |
| CRI                    | > 90                  |
| SDCM                   | 3                     |
| Light beam             | 110°                  |
| Light beam flux        | 2050 lm               |
| Useful light flux      | 1560 lm               |
| Photobiological risk   | 1                     |