ideal lux.



Zeus

General info

Technical - Recessed lights

| Ean | 8021696324845 |
|--------------|-----------------------|
| Item | ZEUS SOURCE 21W 3000K |
| Installation | Recessed lights |
| Warranty | 5 years |
| Gross weight | 0.74 kg |
| Volume | 0.00315 m³ |

Technical info

| Net weight | 0.59 kg |
|--------------------------|--|
| Insulation class | Ш |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C [DO NOT COVER] |
| Dimmer | Non-dimmable, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | Separate, included Replaceable (by qualified operators only), electronic, tridonic |
| Accessories not included | Frame, Reflector, Narrow beam lens, Honeycomb filter, Dimmable driver |

Source info

| Integrated source | Integrated LED module |
|------------------------|---|
| Repleaceable source | Replaceable (by qualified operators only) |
| Power | 21 W |
| Emission | Direct |
| Max consuption | max 21 W |
| Features LED | LED COB CITIZEN |
| CCT LED | 3000 K |
| Duration LED (t. 25°c) | 50000 h |
| CRI | > 90 |
| SDCM | 3 |
| Light beam | 40° |
| Light beam flux | 2100 lm |
| Useful light flux | 1720 lm |
| Photobiological risk | 1 |

