



Info generali

Interno - Applique

Indoor wall mounted adjustable and dimmable lamp with integrated LED sources, in-built switch, in-built integrated battery and direct light emission

| | |
|----------------------|---------------------------------|
| Ean | 8021696350240 |
| Articolo | BEAN AP ROUND RECHARGEABLE NERO |
| Installazione | Applique |
| Garanzia | 5 years |
| Peso lordo | 0.32 kg |
| Volume | 0.00119 m ³ |

Info tecniche e installative

| | |
|--------------------------------|---|
| Peso netto | 0.31 kg |
| Classe di isolamento | III |
| Grado di protezione | IP20 |
| Conformità | CE |
| Temperatura d'esercizio | 0° ~ +40 °C |
| Dimmer | 1, Touch dimmer |
| Alimentazione | 5 V DC 50/60 Hz |
| Alimentatore | Required, separate, not included (power charger, output 5 V DC 2 A USB-C type) electronic |

Info sorgente e prestazionali

| | |
|------------------------------|---------------------------|
| Sorgente integrata | Integrated LED module |
| Sorgente sostituibile | No |
| Potenza | LED 3 W |
| Emissione | Direct |
| Consumo massimo | max 3 W |
| Caratteristiche LED | LED SMD BRIDGELUX |
| CCT LED | 3000 K |
| Durata LED (t. 25°c) | 50000 h |
| CRI | > 95 |
| SDCM | 3 |
| Fascio luminoso | 27° |
| Flusso sorgente | 200 lm |
| Flusso utile | 180 lm |
| Rischio fotobiologico | 2 |
| Potenza in stand-by | < 0.50 W |
| Lampadina inclusa | 1 |
| Lampadina consigliata | LED INTEGRATO 200Lm 3000K |