



## Info generali

### Tecnico - Proiettori e Binari

Indoor track mounted adjustable non-dimmable projector with integrated LED sources and direct light emission

|               |                                          |
|---------------|------------------------------------------|
| Ean           | 8021696267777                            |
| Articolo      | FOX TR 3-PHASE 15W CRI80 4000K ON-OFF BK |
| Installazione | Proiettori e Binari                      |
| Garanzia      | 5 years                                  |
| Peso lordo    | 0.48 kg                                  |
| Volume        | 0.001932 m <sup>3</sup>                  |

## Info tecniche e installative

|                         |                                                                                |
|-------------------------|--------------------------------------------------------------------------------|
| Peso netto              | 0.38 kg                                                                        |
| Classe di isolamento    | I                                                                              |
| Grado di protezione     | IP20                                                                           |
| Conformità              | CE                                                                             |
| Temperatura d'esercizio | 0° ~ +40 °C                                                                    |
| Dimmer                  | Non-dimmable, On-Off                                                           |
| Alimentazione           | 220-240 V AC 50/60 Hz                                                          |
| Alimentatore            | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |
| Accessori non inclusi   | Single connection on-off, Link 3-phase on-off<br>profile                       |

## Info sorgente e prestazionali

|                       |                                           |
|-----------------------|-------------------------------------------|
| Sorgente integrata    | Integrated LED module                     |
| Sorgente sostituibile | Replaceable (by qualified operators only) |
| Potenza               | 15 W                                      |
| Emissione             | Direct                                    |
| Consumo massimo       | max 15 W                                  |
| Caratteristiche LED   | LED COB                                   |
| CCT LED               | 4000 K                                    |
| Durata LED (t. 25°C)  | 50000 h                                   |
| CRI                   | > 80                                      |
| SDCM                  | 3                                         |
| Fascio luminoso       | 41°                                       |
| Flusso sorgente       | 2000 lm                                   |
| Flusso utile          | 1680 lm                                   |
| Rischio fotobiologico | 1                                         |