



Info generali

Tecnico - Proiettori e Binari

Indoor track mounted adjustable non-dimmable projector with integrated LED sources and direct light emission

Ean	8021696348315
Articolo	FOX TR 1-PHASE 15W CRI90 3000K ON-OFF BK
Installazione	Proiettori e Binari
Garanzia	5 years
Peso lordo	0.58 kg
Volume	0.002016 m ³

Info tecniche e installative

Peso netto	0.46 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic
Accessori non inclusi	Link 1-phase profile

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	15 W
Emissione	Direct
Consumo massimo	max 15 W
Caratteristiche LED	LED COB
CCT LED	3000 K
Durata LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Fascio luminoso	39°
Flusso sorgente	1600 lm
Flusso utile	1350 lm
Rischio fotobiologico	1