



Info generali


Tecnico - Lampade da incasso

Indoor wall or ceiling recessed projector with integrated LED sources and direct light emission

Ean	8021696327471
Articolo	QUARK FI 2.8W 3000K WH
Installazione	Lampade da incasso
Garanzia	5 years
Peso lordo	0.05 kg
Volume	0.000413 m ³

Info tecniche e installative

Peso netto	0.02 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C [DO NOT COVER]
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	Separate, included, to be remoted up to 1.3 m distance (does NOT fit into the installation hole) Replaceable (by qualified operators only), electronic



Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	No
Potenza	2,8 W
Emissione	Direct
Consumo massimo	max 2,8 W
Caratteristiche LED	LED SMD BRIDGELUX
CCT LED	3000 K
Durata LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Fascio luminoso	30°
Flusso sorgente	160 lm
Flusso utile	90 lm
Rischio fotobiologico	2