



## Info generali

### Tecnico - Proiettori e Binari

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

|                      |                                            |
|----------------------|--------------------------------------------|
| <b>Ean</b>           | 8021696247991                              |
| <b>Articolo</b>      | QUICK TR 3-PHASE 21W CRI90 4000K ON-OFF WH |
| <b>Installazione</b> | Proiettori e Binari                        |
| <b>Garanzia</b>      | 5 years                                    |
| <b>Peso lordo</b>    | 0.96 kg                                    |
| <b>Volume</b>        | 0.00153 m <sup>3</sup>                     |

## Info tecniche e installative

|                                |                                                                                              |
|--------------------------------|----------------------------------------------------------------------------------------------|
| <b>Peso netto</b>              | 0.76 kg                                                                                      |
| <b>Classe di isolamento</b>    | I                                                                                            |
| <b>Grado di protezione</b>     | IP20                                                                                         |
| <b>Conformità</b>              | CE                                                                                           |
| <b>Temperatura d'esercizio</b> | 0° ~ +40 °C                                                                                  |
| <b>Dimmer</b>                  | Non-dimmable, On-Off                                                                         |
| <b>Alimentazione</b>           | 220-240 V AC 50/60 Hz                                                                        |
| <b>Alimentatore</b>            | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic     |
| <b>Accessori non inclusi</b>   | Honeycomb filter, Narrow or wide beam lens,<br>Single connection on-off, Link on-off profile |

## Info sorgente e prestazionali

|                              |                                           |
|------------------------------|-------------------------------------------|
| <b>Sorgente integrata</b>    | Integrated LED module                     |
| <b>Sorgente sostituibile</b> | Replaceable (by qualified operators only) |
| <b>Potenza</b>               | 21 W                                      |
| <b>Emissione</b>             | Direct                                    |
| <b>Consumo massimo</b>       | max 21 W                                  |
| <b>Caratteristiche LED</b>   | LED COB CITIZEN                           |
| <b>CCT LED</b>               | 4000 K                                    |
| <b>Durata LED (t. 25°C)</b>  | 50000 h                                   |
| <b>CRI</b>                   | > 90                                      |
| <b>SDCM</b>                  | 3                                         |
| <b>Fascio luminoso</b>       | 30°                                       |
| <b>Flusso sorgente</b>       | 2150 lm                                   |
| <b>Flusso utile</b>          | 1900 lm                                   |