



Info generali

Tecnico - Proiettori e Binari

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

Ean	8021696189970
Articolo	SMILE TR 3-PHASE 15W CRI90 50° 3000K WH
Installazione	Proiettori e Binari
Garanzia	5 years
Peso lordo	0.61 kg
Volume	-

Info tecniche e installative

Peso netto	0.61 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Resistenza al carico	IK06
Accessori non inclusi	Honeycomb or Elliptical filter, White decorative ring, Single connection on-off, Link on-off profile

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	15 W
Emissione	Direct
Consumo massimo	max 15 W
Caratteristiche LED	LED COB PHILIPS
CCT LED	3000 K
Durata LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Fascio luminoso	50°
Flusso sorgente	1700 lm
Flusso utile	1410 lm